

E3 Compression Latch Stainless Steel

Material and Finish:

Housing, cap, bushing, shaft and mounting nut:

316 Stainless Steel, passivated. (Tubular cap 303 Stainless Steel, passivated).

Sleeve: 304 Stainless Steel, natural.

Retainer and spring: 302 Stainless Steel, natural.

Pawl: 304 Stainless Steel, passivated

Lockwashers and locknuts: 316 Stainless Steel, passivated.

Cam: 1075 Case Hardened steel.

Dacrosealed[†] pin: 1008 Steel, zinc plated plus yellow chromate dip.

O-Ring and rear seal: Buna-N rubber, natural

Flange gasket: Neoprene, natural.



Product Strength Guidelines:

Flammability Rating (Housing only): UL94 - HB

Operating Temperature Range: -30° C to 115° C

HEAD STYLE	GRIP RANGE		PART NUMBERS [†]	Key Part Numbers
	MIN	MAX		
3mm Double Bitted	16.4	32.2	4.E3-12-10*	4.E3-2-1
	30.4	46.1	4.E3-12-20*	
	43.9	59.6	4.E3-12-30 [†]	
	57.6	73.3	4.E3-12-20*	
	71.3	81.2	4.E3-12-10*	
7mm Triangle	16.4	32.2	4.E3-13-10*	4.E3-2-1
	30.4	46.1	4.E3-13-20*	
	43.9	59.6	4.E3-13-30 [†]	
	57.6	73.3	4.E3-13-20*	
	71.3	81.2	4.E3-12-10*	
South-co [®] Tubular Key	16.4	32.2	4.E3-15-10*	4.E3-5-15
	30.4	46.1	4.E3-15-20*	
	43.9	59.6	4.E3-15-30 [†]	
	57.6	73.3	4.E3-15-20*	
	71.3	81.2	4.E3-15-10*	

HEAD STYLE	GRIP RANGE		PART NUMBERS [†]	Key Part Numbers
	MIN	MAX		
8mm Hex Recess	16.4	32.2	4.E3-16-10*	8mm He Wrench
	30.4	46.1	4.E3-16-20*	
	43.9	59.6	4.E3-16-30 [†]	
	57.6	73.3	4.E3-16-20*	
	71.3	81.2	4.E3-16-10*	
Slotted Recess	16.4	32.2	4.E3-19-10*	—
	30.4	46.1	4.E3-19-20*	
	43.9	59.6	4.E3-19-30 [†]	
	57.6	73.3	4.E3-19-20*	
	71.3	81.2	4.E3-19-10*	
Railway Standard	16.4	32.2	4.E3-111-10*	RIC Standa (European Railway)
	30.4	46.1	4.E3-111-20*	
	43.9	59.6	4.E3-111-30 [†]	
	57.6	73.3	4.E3-111-20*	
	71.3	81.2	4.E3-111-10*	
Bellcore 216	16.4	32.2	4.E3-115-10*	4.E3-12-1
	30.4	46.1	4.E3-115-20*	
	43.9	59.6	4.E3-115-30 [†]	
	57.6	73.3	4.E3-115-20*	
	71.3	81.2	4.E3-115-10*	

* The same pawl (curved forward or reversed) is supplied for both short and long grips.

† For Intermediate grip, straight pawl is supplied.


[†] Individually packaged. For Layer Packed assemblies, 50 piece minimum, sold in multiples of 50, add a -13 to the end of the part number. Eg 4.E3-16-15-13.

Keys (Ordered separately)



4.E3-2-1, 4.E3-3-1,
4.E3-12-1

Die-cast zinc, bright nickel plate or natural with chemical protective film.



4.E3-5-15
Steel, bright nickel pla



HEAD OFFICE
T: +61 02 8887 1200
F: +61 02 8887 1249
E: export@uesint.com

NEW SOUTH WALES
T: +61 02 8787 6500
F: +61 02 8787 6599
E: uesnsw@uesint.com

QUEENSLAND
T: +61 07 3623 5800
F: +61 07 3865 5605
E: uesqld@uesint.com

VICTORIA
T: +61 03 8787 3100
F: +61 03 8787 3101
E: uesvic@uesint.com

SOUTH AUSTRALIA
T: +61 08 8340 1599
F: +61 08 8340 4423
E: uessa@uesint.com

WESTERN AUSTRALIA
T: +61 08 9249 2211
F: +61 08 9249 2022
E: ueswa@uesint.com

NORTHERN TERRITORY
T: +61 08 8946 4500
F: +61 08 8946 4555
E: uesnt@uesint.com

NEW ZEALAND
T: +64 09 633 4019
F: +64 09 633 0249
E: uesnz@uesint.com